



US009410863B2

(12) **United States Patent**  
**Nichols**

(10) **Patent No.:** **US 9,410,863 B2**  
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **TORQUE TOOL CALIBRATION FIXTURE**

(56) **References Cited**

(71) Applicant: **Honda Motor Co., Ltd.**, Tokyo (JP)

U.S. PATENT DOCUMENTS

(72) Inventor: **Thomas R. Nichols**, Wellington, AL  
(US)

4,171,647	A	10/1979	Herrgen
4,583,411	A	4/1986	Hales
5,099,678	A	3/1992	Grabovac et al.
5,181,425	A	1/1993	Livingston
7,885,780	B2	2/2011	Lucke
8,117,887	B2	2/2012	Schwafertz et al.

(73) Assignee: **Honda Motor Co., Ltd.**, Tokyo (JP)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 423 days.

Primary Examiner — Robert R Raeviss

(74) Attorney, Agent, or Firm — Rankin, Hill & Clark LLP

(21) Appl. No.: **14/105,225**

(22) Filed: **Dec. 13, 2013**

(65) **Prior Publication Data**

US 2015/0168245 A1 Jun. 18, 2015

(51) **Int. Cl.**  
**G01L 25/00** (2006.01)  
**G01L 5/24** (2006.01)

(52) **U.S. Cl.**  
CPC **G01L 25/003** (2013.01); **G01L 5/24** (2013.01)

(58) **Field of Classification Search**  
None  
See application file for complete search history.

(57) **ABSTRACT**

A torque tool calibration fixture includes a support and a mounting plate movably secured thereto. The plate is configured to have a torque tool mounted thereto for calibration. A transducer is secured to the mounting plate for movement therewith. The transducer has one end portion configured to be coupled to a drive end of a head portion of the associated torque tool and an opposite end portion. A joint assembly is fixed to the support and coupled to the opposite end portion of the transducer. The joint assembly defines a rotational axis and the mounting plate is movable along the rotational axis. A torque analyzer is in communication with the transducer. Rotation of the joint assembly results in the joint assembly forming a hard joint where further rotation of the joint assembly is prevented. The analyzer indicates actual exerted torque on the hard joint as measured by the transducer.

**20 Claims, 5 Drawing Sheets**

